





LIGHTLIFT 15.70 *PERFORMANCE III S*



LIGHTLIFT 15.70 *PERFORMANCE III*



LIGHTLIFT 15.70 *PERFORMANCE III S*

PETROL ENGINE

Brand.....HONDA
 TypeiGX390
 Pistons no. and displacementsingle-cylinder 389 cc
 Max. gross power. 11,7 HP - 8,7 kW @ 3600 rpm
 Electrical start 12 volt

DIESEL ENGINE

BrandHATZ
 Type.....1B40 - HD Autorev
 Pistons no. and displacementsingle-cylinder 462 cc
 Max. gross power. 10 HP - 7,5 kW @ 3600 rpm
 Electrical start 12 volt

ELECTRIC MOTOR

Standard230V / 50 Hz - 2,2 kW
 Optional 110V / 50 Hz - 2,2 kW

HYDRAULIC PUMPS

Pump diesel engineno. 2 gear pumps
 Pump electric motorno. 2 gear pumps

TRACKED UNDERCARRIAGE

Track tensionergrease-filled
 Rollers no. per side3 + slide
 Widening system.....748 / 1100 mm
 Translation speed (thermic engine) with 2nd auto2speed..... 1,4 - 2,6 km/h

WEIGHT MACHINE PETROL ENGINE 1950 kg
 MAX UPPER SLANT16° / 28,7%
 MAX WIND SPEED 12,5 m/s

LIGHTLIFT 15.70 *PERFORMANCE III* LITHIUM *ION*

ELECTRIC SYSTEM

Electric system voltage.....	36V-12V
Lithium battery pack.....	3,6 KWh
Autonomy (continuous cycle)*.....	4-5 h
Onboard battery charger	220V 50Hz
Optional battery charger	110V 50Hz
Recharge time on flat batteries.....	4 h (indicative)
Recharge time to 80% on flat batteries.....	2 h (indicative)

HYDRAULIC PUMPS

Electric motor	no.2 gear pumps
----------------------	-----------------

TRACKED UNDERCARRIAGE

Track tensioner	grease-filled
Rollers no. per side	3 + slide
Widening system.....	748 / 1100 mm

MAX UPPER SLANT16° / 28,7%

MAX WIND SPEED12,5 m/s

* (Autonomy measured with Hinowa H2 operating cycle)